



**MOD. NIAGARA**

H the minimum value of 760 (30")  
 H the maximum value of 1500 (60")

No.	Name	Qty	Material	REMARK	Drawing No.
1	Handwheel	1	DI	ASTM A126	APC-QSCZG-05
2	Driving rod	1	S. S. 304	ASTM A276	APC-ZSQ-02
3	Indicator cover	1	CI	ASTM A126	APC-ZSQ-05
4	Pin	1	1035	ASTM A29	
5	Driving nut	1	S. S. 304	ASTM A276	APC-ZSQ-03
6	Bolt	4	1035	ASTM A29	
7	Screwed plug	1	1035	ASTM A29	G 1/2"
8	Connecting rod	1	1035	ASTM A29	30X30X3X1200
9	Connecting rod	1	1045	ASTM A29	40X40X3X1450
10	Extension rod	1	A283 Gr. C	ASTM A36	APC-ZSQ-12
11	Flange	1	CI	ASTM A126	APC-ZSQ-07
12	Connecting rod	1	1045	ASTM A29	50X50X4X50
13	Connecting rod	1	1045	ASTM A29	60X60X3X100
14	Bolt	1	1035	ASTM A29	M10X75
15	Bolt	2	1035	ASTM A29	3/4"-10
16	Bolt	2	1035	ASTM A29	3/4"-10
17	Indicator plate	4	A413.0	ASTM S12A	APC-ZSQ-04
18	Keyhole plate	2	A283 Gr. C	ASTM A36	APC-ZSQ-11
19	Keyhole plate gasket	2	EPDM	ASTM D2000	APC-ZSQ-10
20	Indicator flap	2	Organic glass		APC-ZSQ-09
21	Housing	1	CI	ASTM A126	APC-ZSQ-01
22	Bolt	2	1035	ASTM A29	5/8"-11

TOLLERANZE / TOLERANCES		INDICE		NATURA DELLA MODIFICA		DATA		FIRMA	
LUNGHEZZA / LENGTH	ANGOLI / ANGLES	SMUSI / ROUNDS	RAGGI / RADIUS						
UNI - ISO 27188	m	DENOMINAZIONE / DENOMINATION							
<b>POST INDICATOR VERTICALE</b>									
FORI / HOLES H13		ALBERI / SHAFTS H13		SCALA / SCALE		MATERIALE / MATERIAL		DEGNATO / DRAWN DATA	
								VM 05/06/2020	
<b>ZIGGIOTTO &amp; C.</b> RONCO ALL'ADIGE VERONA - ITALIA				DUREZZA / HARDNESS		PESO / WEIGHT		VERIFICATO / CONTROLLED DATA	
				RESISTENZA / STRENGTH		TRATTAMENTO / TREATMENT		CODICE / CODE	
								Sch-Art 402_VERTICALE Rev.3	

A termini di legge è vietato l'uso, la divulgazione e la riproduzione senza l'autorizzazione scritta della ZIGGIOTTO & C.