

Art. S80 SPRINKLER PENDENT “STANDARD RESPONSE”

Sprinkler pendent standard response

Caratteristiche / Specifications

- Per tutte le classi di pericolo / All Hazards
- Bulbo da 5 mm / 5 mm bulb

Aree di utilizzo / Usage areas

- Casa / House
- Centro commerciale / Mall
- Hotel / Hotel
- Dormitorio / Dormitory
- Ospedale / Ospedale
- Sala convegni / Trade Center




Ref.
2831

Cert/LPCB
Ref. 1402a

Sono adatti per controsoffitti o luoghi indicati per sprinkler rivolti verso il basso. L'acqua spruzza ad espansione conica. Possono essere utilizzati con rosette.

They are preferred in suspended ceilings or in locations where downward sprinklers are appropriate. Water sprays in a conically expansion. They can be used with escutcheons.

Articolo catalogo /Catalogue Code	S80 - 1/2"	S/80 - 3/4"
Fattore K/K Factor	K5.6(80),	K8.0(115)
Dimensione del filetto/Thread size	1/2" NPT (15 mm)	3/4" NPT (20 mm)
Risposta/Response	Risposta Standard / Standard Response	
Finitura/Finishes	Ottone, Cromo, Bianco / Brass, Chrome, White	
Temperatura/Temperature	57°C (135°F), 68°C (155°F), 79°C (175°F), 93°C (200°F), 141°C (286°F), 182°C (360°F)	



Rev,0 del 29.02.24