



Technical requirements

- Design standard: ANSI/AWWA C502
- Nominal pressure: 250PSi.
- Connecting thread of fire truck is 4.5—4NH, 2 thread connector of soft pipe is 2.5—7.5NH
- Flange connector: EN 1092 DN150 PN16/ ANSI 150

POSSIBILITA' DI FORNIRE L'IDRANTE ANCHE CON USCITE UNI

L	3'6"	4'	4'6"	5'	5'6"	6'	6'6"	7'
	1063	1215	1368	1520	1673	1825	1978	2130

No.	Name	Qty	Material	Remark	Drawing No.	Version No.
38	Bolts	2	304	ASTM A240		Figure not shown
37		1	304	ASTM A240		MH-XHS-39 02
36	Check turn gasket	1	G-B	ASTM A283-B		MH-XHS-34 01
35	Locking nut seat	1	DI	ASTM A536		MH-XHS-38 01
34	Platen	1	DI	ASTM A536		MH-XHS-33A 01
33	Annular tubes	1	1045	ASTM A29\29M		MH-XHS-37 01
32	Nuts&Bolts	6	1035	ASTM A29\29M		
31	Seat fixing plate	1	DI	ASTM A536		MH-XHS-31 01
30	Nuts&Bolts	2	304	ASTM A240		
29	Seat	1	C95400	ASTM B148		MH-XHS-29A 01
28	Drain hole Cover	1	C95400+EPDM			MH-XHS-40 01
27	Cushion rubber	1	EPDM			MH-XHS-27 01
26	Screw stem	1	1045	ASTM A29\29M		MH-XHS-26 01
25	Nuts&Bolts	8	1035	ASTM A29\29M		
24	Cover chain	3	G-B	ASTM A283-B		MH-XHS-24 01
23	Cylindrical pin	1	1045	ASTM A29\29M		MH-XHS-23 01
22	Cover DN100	1	DI	ASTM A536		MH-XHS-22 01
21	Nuts&Bolts	8	1035	ASTM A29\29M		
20	Screw nut seat	1	C95400	ASTM B148		MH-XHS-20A 01
19	Screw nut gasket	1	C95400	ASTM B148		MH-XHS-19A 01
18	Screw stem nut	1	C95400	ASTM B148		MH-XHS-18A 01
17	Thread plug	1	C95400	ASTM B148		MH-XHS-17A 01
16	Upper end cover	1	DI	ASTM A536		MH-XHS-16A 01
15	Cover DN65	2	DI	ASTM A536		MH-XHS-15 01
14	Cover gasket DN65	2	EPDM			MH-XHS-14 01
13	Connector DN65	2	C95400	ASTM B148		MH-XHS-13A 01
12	Upper body	1	DI	ASTM A536		MH-XHS-12 01
11	Clump for connection tube	1	DI	ASTM A536		MH-XHS-11 01
10	Connecting rod sleeve	1	1045	ASTM A29\29M		MH-XHS-10 01
09	Perforated cylindrical pin	2	1045	ASTM A29\29M		MH-XHS-09 01
08	Connecting cylinder	1	DI	ASTM A536		MH-XHS-08 02
07	Drain hole spring	2	316	ASTM A240		MH-XHS-41 01
06	Sealed rubber sheet	1	EPDM			MH-XHS-06A 01
05	Tray	1	DI	ASTM A536		MH-XHS-05A 01
04	Locking nut gasket	1	EPDM			
03	Connecting rod	1	1045	ASTM A29\29M		MH-XHS-03 02
02	Locking nut	1	DI	ASTM A536		MH-XHS-02 01
01	Flange connector	1	DI	ASTM A536		MH-XHS-01B 01

TOLLERANZE / TOLERANCES	INDICE	NATURA DELLA MODIFICA	DATA	FIRMA										
<table border="1"> <tr><td>LIVINEZZA / FINISH</td><td>INDICE / INDEX</td><td>INDICE / INDEX</td><td>INDICE / INDEX</td><td>INDICE / INDEX</td></tr> <tr><td>UNI - ISO 27168 m</td><td>ALBERI / SHAFTS H13</td><td>SCALA / SCALE MATERIALE / MATERIAL</td><td></td><td></td></tr> </table>	LIVINEZZA / FINISH	INDICE / INDEX	INDICE / INDEX	INDICE / INDEX	INDICE / INDEX	UNI - ISO 27168 m	ALBERI / SHAFTS H13	SCALA / SCALE MATERIALE / MATERIAL						
LIVINEZZA / FINISH	INDICE / INDEX	INDICE / INDEX	INDICE / INDEX	INDICE / INDEX										
UNI - ISO 27168 m	ALBERI / SHAFTS H13	SCALA / SCALE MATERIALE / MATERIAL												

ZIGGIOTTO & C.
 RONCO ALL'ADIGE
 VERONA - ITALIA

PILIAR DRY UL/FM HYDRANT DN150 MOD. COLORADO

DIREZZA / HARDNESS PESO / WEIGHT
 RESISTENZA / STRENGTH TRATTAMENTO/TREATMENT
 dis-ART407 REV.2

A. Terminali di legge e vendita fuori, in delegazione e in riproduzione senza autorizzazione scritta dalla ZIGGIOTTO & C.