

# Art. S80 SPRINKLER PENDENT “STANDARD RESPONSE”

## Sprinkler pendent standard response

### Caratteristiche / Specifications

- Per tutte le classi di pericolo / **All Hazards**
- Bulbo da 5 mm / **5 mm bulb**

### Aree di utilizzo / Usage areas

- Casa / **House**
- Centro commerciale / **Mall**
- Hotel / **Hotel**
- Dormitorio / **Dormitory**
- Ospedale / **Ospedale**
- Sala convegni / **Trade Center**



Ref. 2831  
Cert/LPCB  
Ref. 1402a

Sono adatti per controsoffitti o luoghi indicati per sprinkler rivolti verso il basso. L'acqua spruzza ad espansione conica. Possono essere utilizzati con rosette.

They are preferred in suspended ceilings or in locations where downward sprinklers are appropriate. Water sprays in a conically expansion. They can be used with escutcheons.

| Articolo catalogo /Catalogue Code  | S80 - 1/2"   | S/80 - 3/4"      |
|------------------------------------|--|------------------|
| Fattore K/K Factor                 | K5.6(80),  | K8.0(115)        |
| Dimensione del filetto/Thread size | 1/2" NPT (15 mm)   | 3/4" NPT (20 mm) |
| Risposta/Response                  | Risposta Standard / <b>Standard Response</b>                                   |                  |
| Finitura/Finishes                  | Ottone, Cromo, Bianco / <b>Brass, Chrome, White</b>                            |                  |
| Temperatura/Temperature            | 57°C(135°F), 68°C(155°F), 79°C(175°F), 93°C(200°F), 141°C(286°F), 182°C(360°F) |                  |



Rev,0 del 29.02.24